

ypressure Jenny Gas Engine Direct Drive Cold Pressure Washers

were designed and manufactured to be rugged, dependable,

HPJ-3040

efficient, versatile, safe and easy to use. The HPJ's heavy duty roll cage frame construction and finest

HYPRESSURE JENNY WASHERS

Problems Worldwide

quality components available make them ideally suited for the rigorous demands of commercial, industrial and rental applications.

These high performance machines are packed full of standard

features to let you clean both quickly and effectively.

Put the power of a Hypressure Jenny to work wash-

ing equipment, cleaning vehicles and fleets, or helping with general housekeeping tasks. The HPJ's allow you to clean with no wasted time, effort or water. Exact cleaning needs can be met by combining a range of pressures from 2000 to an amazing 5000 psi and flows from 2.8 gpm to 8.0 gpm.

The machine is ready to use straight out of the box! Just add oil to the engine, fill the tank with gasoline, connect the water supply hose, start the engine and begin cleaning.



Simplicity

Jenny's Hypressure Series of Gas Engine Cold Pressure Washers are very easy to operate. Simply connect the unit to a water supply, connect the quick coupled cleaning gun and hose, start the engine and begin cleaning. It's that easy!

Quality

The trademark of Jenny Cleaning Equipment has been Quality since steam cleaning was invented by us in 1927. These American made machines feature only the finest pumps, engines and accessories available and the best manufacturing methods and techniques. All Jenny machines are tested to ensure they perform to our exacting standards and specifications.

Serviceability

The units were designed to allow easy access to all of the major components. Oil changes on the pump, gearbox and engine are simple and quick. Cleaning the high capacity inlet water filter is as simple as unscrewing the cartridge, emptying it out and replacing it. As with all Jenny machines, parts and accessories are always readily available.



Gasoline Tank with **Fuel Gauge** and Quick Connects

HPJ-3540



Pump and Water System

In manufacturing the machines, only the highest quality components are used to ensure years of trouble free service. The high performance Over Head Valve Kohler Command Series engines are American made. They all feature low oil shut-off and the 11 Hp and larger engines come standard with a pressurized oil system and oil filter. The industrial grade pumps used on the units are all triplex ceramic plunger pumps, constructed of the highest quality materials under very tight tolerances assuring long term

performance, and are protected from both extreme

pressure and temperature conditions by specially designed temperature and pressure relief valves.

Durability

The heavy duty powder coated roll cage frame was designed to be compact, portable and able to withstand years of rugged and punishing use. The maneuvering handle and the solution container holder fold inward to allow the unit to be more compact and protect the motor and optional detachable 3 gallon gasoline tank. The unit comes complete with pneumatic tires with ball bearing hubs, wheel brake, built-in easy mount hose reel adapter, plastic battery box (electric start units only), and a convenient nozzle holder with four different color coded pressure nozzles and one soap nozzle.

	HPJ2030	HPJ2545	HPJ2580	HPJ3035	HPJ3040	HPJ3056	HPJ3540	HPJ3555	HPJ4040	HPJ4045	HPJ5045
Pump Output											
Pressure – PSIG	2000	2500	2500	3000	3000	3000	3500	3500	4000	4000	5000
Volume – GPM	2.8/3.0	4.5	8.0	3.5/3.5	4.0/4.0	5.6	4.0	5.5	4.0	4.5	4.5
Triplex Ceramic Plunger	General/Cat	General	Cat	General/Cat	General/Cat	General	Cat	Cat	General	Cat	Cat
Direct Drive	Standard	Standard	Gear Reduced	Standard	Standard	Gear Reduced	Standard	Gear Reduced	Gear Reduced	Gear Reduced	Gear Reduced
Gasoline Engine Horsepower	6 HP OHV	13 HP OHV	20 HP OHV	11HP OHV	13 HP OHV	18HP OHV	15 HP OHV	20 HP OHV	18 HP OHV	20 HP OHV	25 HP OHV
Starting	Recoil	Recoil	Electric	Recoil	Recoil	Electric	Recoil	Electric	Electric	Electric	Electric
Oil Sentry	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Oil Cartridge Filter	N/A	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
In-Line Gasoline Filter	N/A	N/A	Standard	N/A	N/A	Standard	N/A	Standard	Standard	Standard	Standard
Fuel Tank Capacity	3 Quart	1.25 Gallon	3 Gallon	1.25 Gallon	1.25 Gallon	3 Gallon	1.25 Gallon	3 Gallon	3 Gallon	3 Gallon	3 Gallon

Note: There may be slight variances in gallonages, pressure, and amp draw due to variances allowed by manufacturers of our machine components. We attempt to keep the machine performance =/±5% of listed specifications.

Features standard to all units:

- · Heavy Duty Powder Coated Roll Cage Frame Construction
- · Fold Down or Slide Out Maneuvering Handle
- · Pneumatic Wheels
- · Nozzle Control
- Thermal Pump Protection
- · High Pressure Relief Valve
- · High Capacity Inlet In-Line Water Strainer
- · Low Pressure Adjustable Chemical Injection
- 0, 15, 25, 40 Degree Pressure Wash Nozzles and 1 Brass Soap Tip
- 3/8" Diameter x 50 Foot Hose with **Quick Coupling**
- · Hose Reel Mounting Adapter

Optional Accessories:

- High Speed Rotary Nozzle
- · Variable Pressure Dual Lance Wand
- · 25, 50 and 100 Foot Extension Hoses
- 13" or 16" Diameter Hose Reels
- Rotary Brush
- 3 Gallon Gasoline Tank with Quick Connects on 11, 13 and 15 Hp Units (Factory installed)
- · Electric Start with Plastic Battery Box on 11, 13 and 15 Hp Units
- · Additional 3 Gallon Fuel Tank with Fuel Gauge and Quick Connects

